

## H-x244-GST - E-X-P Complete Ultra-Compact Tankless Water Heater Service Valves Kits

### H-x244WPR-GST Series

#### E-X-P Complete Tankless Water Heater Installation Kit

Includes E-X-P Ultra Compact Service Valves  
w/ LF Residential Pressure Relief Valve  
(150 PSI / 1.163M BTU/HR)  
& 3/4" FIP Full Port Forged Brass Gas Sediment Trap  
w/ 3/4" FIP Gas Ball Valve & 24" Flex Line  
Lead-Free



### Certifications

Certified to NSF/ANSI 61 & 372, ANSI Z21.15, CSA 9.1 - Applies to TWH Service Valves and Gas Valve (Flex Line: ANSI Z21.24 & CSA 6.10)



| Size (in)                    | Item#          | Weight (lbs) | CTN Qty | Case Qty | BTU                                                                       |
|------------------------------|----------------|--------------|---------|----------|---------------------------------------------------------------------------|
| <b>FIP Union x F1807 PEX</b> |                |              |         |          | <b>250 PSI CWP Max (GST 1/2 PSI Max)</b> <b>200°F Max (GST 149°F Max)</b> |
| 3/4"                         | H-12443WPR-GST | 5.10         | 1       | 4        | 290000                                                                    |
| <b>FIP Union x F1960 PEX</b> |                |              |         |          | <b>250 PSI CWP Max (GST 1/2 PSI Max)</b> <b>200°F Max (GST 149°F Max)</b> |
| 3/4"                         | H-32443WPR-GST | 5.21         | 1       | 4        | 290000                                                                    |
| <b>FIP Union x FIP</b>       |                |              |         |          | <b>250 PSI CWP Max (GST 1/2 PSI Max)</b> <b>200°F Max (GST 149°F Max)</b> |
| 3/4"                         | H-42443WPR-GST | 6.24         | 1       | 4        | 290000                                                                    |
| <b>FIP Union x SWT</b>       |                |              |         |          | <b>250 PSI CWP Max (GST 1/2 PSI Max)</b> <b>200°F Max (GST 149°F Max)</b> |
| 3/4"                         | H-52443WPR-GST | 6.18         | 1       | 4        | 290000                                                                    |

See website for complete specifications for individual product components.

