



Forum™ Traverse®

60" x 36" Vikrell bath/shower with AIP backerboards,
grab bars, & bath seat, right drain
71620125



Features

- Tongue-and-groove modular design allows for easy installation during any phase of construction
- Modern subway tile design
- Full-length shelf provides generous storage
- Factory-installed Aging in Place backerboards for future grab bar installation
- Five-piece grab bar kit
- 16" x 22" (406 x 559 mm) bath seat with telescoping legs and non-slip feet clamps securely to bath
- Innovative Dry-Block™ seal and channeled water containment system form watertight seams

Material

- Compression-molded from our exclusive solid Vikrell® material

Installation

- Pro4™ installation system features a two-piece back wall design, enabling one-person handling and installation
- Alcove
- Right drain
- Caulk-free installation

Included Components

- 71504106 60" x 36" Vikrell® bath/shower wall set with Aging in Place backerboards
- 71577103 5-Piece ADA-adaptable grab bar kit
- 71607104 16" x 22" bath seat
- 71621120 60" x 36" Vikrell® alcove bath, right drain



ADA

Codes/Standards

CSA B45.5/IAPMO Z124
ASTM E162
ASTM E662
ADA
ICC/ANSI A117.1

STERLING® Vikrell® or Acrylic Baths and Shower Bases Ten-Year Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color Code Description


	0	White
---	---	-------

1-800-STERLING (1-800-783-7546)

Kohler Co. reserves the right to make revisions without notice to product specifications.

For the most current Specification Sheet, go to www.sterlingplumbing.com.

2-20-2025 22:42 - US



Technical Information

All product dimensions are nominal.

Drain location:	Right
Weight:	170 lbs (77.1 kg)
Water depth:	13-1/4" (337 mm)
Water capacity:	61 gal (230.9 L)
Minimum flat for door:	3" (76 mm)
Maximum door height:	56-3/4" (1441 mm)
Maximum door width:	57-5/8" (1464 mm)

Notes

Install this product according to the installation instructions.

ADA compliant when installed to the specific requirements of these regulations.